



METHOD AND DEVICE FOR RECORDING OF INFORMATION

5

TECHNICAL FIELD OF THE INVENTION

The present invention relates to a method and a device for recording of text by imaging the text on an optical sensor in a handheld device, said sensor being intended for digital recording of images.

BACKGROUND OF THE INVENTION

It is sometimes desired to abstract parts of text or image information in a document which may later be edited using appropriate software in a computer. A known method of inputting text and image information into a computer is to use a stationary or portable scanner.

A stationary scanner is suitable for entering entire pages with text and image information, the scanner being automatically passed across the page at a constant speed. This type of scanner is not suited for inputting selected parts of information on a page.

A portable, handheld scanner may be used any time interesting information is to be scanned, but normally has a limited field of view.

US-5,301,243 discloses a hand-held scanner for reading characters from a string of characters on a substrate. The scanner is moved in contact with the substrate along the character line and has an optical system which images a small part of the substrate. The optical system comprises a CCD type line sensor provided with a plurality of light-sensitive elements arranged in a line. When the scanner is passed across the characters on the substrate, a succession of vertical slices of the characters and of the spaces between them is recorded. The slices are stored in the scanner as a digital bit-map image. OCR software (OCR = Optical Character Recognition)

is then used to identify the characters and store them in character-coded form, such as ASCII code. The character recognition can be made either in the scanner or in an external computer to which the bit-map image is sent.

5 Another type of hand-held scanner for inputting text is disclosed in US-4,949,391. This scanner has a two-dimensional sensor which records images of the underlying surface as the scanner is being moved across the same. The scanner is restricted to movements in a direction
10 which is determined by a wheel in contact with the surface. Before the recorded images are assembled into a composite image, redundant information is removed from the images. The composite image can be analyzed in a computer for identification of characters.

15 A drawback with the handheld scanners described above is that their field of view is relatively small. In order to record a large amount of information, such as passages consisting of several lines, a user must therefore move the scanner back and forth across the
20 surface repeatedly. Moreover, the movement has to follow a predetermined path, such as along the lines of text.

Publication WO 99/57678 discloses a device for recording information from a substrate. The device may
operate in two modes, one scanner mode, in which lines of
25 text is scanned, and a photograph mode, in which separate pictures are taken of a document or an object.

Publication WO 98/20446 discloses a scanner pen, which is adapted to be moved over a line of text for scanning the text. As the pen moves over the text image,
30 several pictures are taken of the text. The pictures are processed by a computer and assembled or stitched together for forming a composite image of the entire line of text, which cannot be read by a single picture. The scanner pen can only scan a single line of text at each
35 time.

Thus, there is a need for a handheld scanner pen of the above-mentioned type which is adapted to scan several

lines of text simultaneously as well as smaller pictures.

SUMMARY OF THE INVENTION

5 An object of the present invention is to provide a scanner pen which enable fast recording of text in real time.

10 Another object of the invention is to provide a scanner pen which may be used at a distance from the text and may scan several lines of text in a single stroke as well as discrete pictures.

These objects are obtained by a method and a device for recording information by imaging on a light-sensitive sensor for obtaining at least two images of the information having partially overlapping contents. The
 15 method comprises converting the information in each of the images to a coded representation, comparing the coded representation of said images for determining an overlap position, and assembling the images to form a composite image. The coded representation may be a character code, such as ASCII. Alternatively, the coded representation
 20 may comprise a division of the information inside borders, such as rectangles, each comprising portions of the information, such as words included in said information. Thereafter, the composite image may be
 25 converted to a character code format, such as ASCII-code. Alternatively, each image may be separately converted into character code format, such as ASCII, before assembling.

The method may further comprise determining structures in each of said images, such as direction of
 30 lines or text line directions in each image. This may be accomplished by means of a Hough transformation of each image. This information may be used for adjusting the rotational position and/or perspective of each image in dependence of the direction of lines. The information may
 35 also be used for the division of the image in reactangles.

A concept of the present invention is to record a

plurality of images of a text, said images overlapping each other, each image comprising several lines of text. Subsequently, OCR (Optical Character Recognition) is carried out as regards the recorded images, resulting in

5 sets of characters. The sets of characters may contain a number of characters indicating "end of line" if the text comprises several lines. Then the sets of characters are assembled using the characters in the sets of characters. An advantage of this mode of operation is that relatively

10 large images can be recorded at a time, without the assembling of the images being cumbersome since the images are converted into character codes before being assembled. The effective resolution is small in a set of characters compared to a bit-map image, thus saving

15 computing power. The effective resolution in the set of characters is a single character. Thus, assembling in two dimensions may be possible with the present invention in a handheld device.

The lines of text in two subsequent images do not

20 necessarily coincide in the vertical direction. The first line in a first recorded image may correspond to the second line in a second recorded image. However, the assembling will adjust the vertical position so that correct assembling is obtained.

25 By a set of characters is meant a plurality of characters, from which the relative positions of the characters can be determined. The set of characters may be a string of characters comprising characters for blank and end of line.

30 A device for recording a text images the text on a light-sensitive sensor with a two-dimensional sensor surface, which sensor is intended for digital recording of images of the text, said images having partly overlapping contents. The device is characterized in that

35 it is adapted to convert at least two of the images recorded by the sensor into a set of characters each, comprising a plurality of characters, by means of

character recognition. The device is adapted to subsequently assemble the sets of characters with the aid of the characters in the sets of characters.

- By carrying out character recognition before
- 5 assembling the images, the operation of assembling large images at pixel level can be omitted. Moreover, there is less risk that a character would not be recognized owing to poor assembling, which may be the case when digital images are assembled in pixel level and then character
- 10 recognition is carried out in an area that is overlapped by both images that are assembled. Then, the character may be distorted if the assembling is not carried out properly, which may results in that the character is not recognized in the character recognition process.
- 15 According to this invention, the character recognition process take advantage of the original quality of the image for character recognition. By first converting the images into sets of characters, the actual assembling of the sets of characters may be quick since the number of
- 20 characters is considerably smaller than the number of pixels in the recorded images.

- Moreover, by OCR interpretation of each image before the assembly thereof, a plurality of OCR interpretations of the same character will be obtained, one for each
- 25 image where the character is included, and the interpretation which gives highest recognition probability can be selected.

- Alternatively, it is possible to assemble the sets of characters using words in the set of characters. Thus,
- 30 entire words in one of the sets of characters that are to be assembled are compared with words in the other of the sets of characters that are to be assembled. When assembling words, it may be required to compare each individual character.

- 35 By word is meant a plurality of characters which also includes special characters. The special characters are, for example, blank, full stop, comma or end of line.

The method may comprise finding the lines of text in the recorded images, to find start and end of words along the lines of text and to select which of the recorded images are to be converted into sets of characters with the aid of the identified start and end of the words in the recorded images, so that only images with the necessary information are converted into sets of characters or that images with duplicate information may be discarded. By identifying start and end of the words along the lines of text, it will be possible to make a rough assembling of the images without first making optical character recognition. When the start and end of the words have been identified, the recorded images are corrected as regards rotation and perspective. By making a rough assembling of the images, it will be possible to find out how the images overlap each other. The images which contain only information that is available completely in other images then need not be converted into sets of characters.

Start and end of words along the lines of text may be identified by searching, in each pixel along a line through the lines of text, for the number of dark pixels a predetermined number of pixels up and down from the line of text. An end of a word being defined as if there are no dark pixels in a predetermined number of pixels above and below the line of text, i.e. there are blanks. To manage italics one may alternatively search along an oblique line. It is, of course, possible to search for white pixels, instead of dark pixels, if the text should be brighter than the background, i.e. inverted.

The images may be converted into binary images, i.e. images containing merely black and white, since this facilitates the continued image processing.

Moreover, the method may comprise finding the lines of text in the recorded images using the Hough transformation of the recorded images. The Hough transformation can briefly be described as follows. There

is an infinite number of straight lines extending through a point in an XY plane. The equation of the straight line for each of these lines can be expressed with two parameters. If the parameters of the individual lines are plotted in a diagram, a curve is obtained which corresponds to the Hough transform of the point. In this way, it is possible to plot curves for any of the points in the XY plane. The Hough transform of two different points will intersect in a point, which corresponds to the equation of the straight line extending through the two points. If the Hough transforms for all the dark pixels in a recorded image are plotted, a large number of intersections between the different Hough transforms will be obtained. However, there is a maximum number of intersections for lines following the lines of text.

The device may comprise a memory adapted to store the recorded images, which are to be converted into sets of characters, in the memory, and to convert the stored images into sets of characters after completion of the recording of the images. By only storing the recorded images which are to be converted into sets of characters, the memory space which is required for storing recorded images is minimized. By converting the stored images into sets of characters after the recording of images has been completed, it is not necessary to place high demands on the speed of the optical character recognition, which would be the case if it were to be carried out while images are being recorded.

The device is advantageously designed in such a manner that a user can hold it by hand and at a distance from a substrate to record text on the substrate.

The device may be adapted to correct the images for rotation before they are converted into sets of characters. In the case where the lines of text in the recorded images have been identified, the correction for rotation can be carried out in a relatively simple way. However, some optical character recognition programs can

process also rotated images, in which case the rotation is not required.

Correspondingly, the device may correct the images for perspective before they are converted into sets of characters since the optical character recognition may be facilitated if all letters have the same size in the images.

The device may be designed as a reading head which is connected to a calculating unit in which the recorded images are processed.

The device may be adapted to assemble the sets of characters by comparing the sets of characters in pairs, the sets of characters being compared in a number of relative positions displaced relative to each other. Thus, a first character in a first set of characters is compared with characters in the second set of characters until correspondence is achieved or until the first character in the first set of characters has been compared with all characters in the second set of characters. Subsequently, the correspondence of the second characters in the first set of characters is compared with the characters in the second set of characters. By making the comparison for a large number of different relative positions, a plurality of total numbers of points can be obtained, the total number of points reflecting the correspondence between the two sets of characters for the specific position. In this way, an optimum relative position can be obtained.

The device may be adapted to store the recorded images that are to be converted into sets of characters along with a serial number indicating in which order the images have been recorded, and to assemble the sets of characters with the aid of the serial number for the images corresponding to the sets of characters. Especially in the case where first all images are recorded and not until then the character recognition and the assembling are begun, the serial numbers may be used for

the recorded images since then a large number of images are to be assembled.

According to a second aspect of the present invention, a method is provided for recording of text on a substrate, comprising the step of imaging and digitally recording images of the text, the images having partly overlapping contents. The method is characterized in that it comprises the steps of converting at least two of the recorded images into a set of characters, each with a plurality of characters, by means of optical character recognition, and putting together the sets of characters with the aid of the characters in the sets of characters.

The area recorded by the sensor may be arranged so that a plurality of lines of text are imaged in a recorded image.

According to a third aspect of the present invention, a computer-readable storage medium, in which a computer program is stored which is adapted to be used for conversion of digital images, which are recorded by an image sensor, into text. The storage medium is characterized in that the computer program comprises instructions for making the computer receive digital images as input signals, convert the digital images into sets of characters, with a plurality of characters, by means of character recognition, and put together the sets of characters with the aid of the characters in the sets of characters.

Further objects, features and advantages of the invention will appear from the following detailed description of embodiments of the invention with reference to the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a schematic view of a device according to a first embodiment of the present invention.

Fig. 2 is a schematic block diagram of parts of the embodiment of Fig 1.

Fig. 3 is a schematic view of images of text on a sheet of paper, which are recorded according to the invention.

5 Figs. 4a and 4b are diagrams, illustrating the principle of the Hough transformation.

Fig. 5 is a diagram, which shows maximum points for the Hough transform of two different images.

Fig. 6 is a diagram and a histogram for illustrating the detection of start and end points of words.

10 Figs. 7a and 7b are diagrams for illustrating the division of the text images into words.

Fig. 8 is a diagram of two images converted to characters for assembling.

15 Fig. 9 is a diagram for illustrating lines of text in a recorded image.

Fig. 10 is a flow chart of the operation of a computer program according to the invention.

20 Fig. 11a, 11b and 11c are shematic representations of a text, division thereof in rectangles and display on a small display.

DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

Fig. 1 discloses a scanner pen, comprises a casing 1 having approximately the same shape as a conventional 25 highlighter. In one short side of the casing there is an opening 2, which is intended to be directed at an area on a substrate which a user wants to image. The information carrier can be a sheet of paper.

30 The casing 1 essentially contains an optics part 3, an electronic circuitry part 4 and a power supply part 5.

The optics part 3 comprises a lens system 7, light-emitting diodes 6, and an optical sensor 8 constituting an interface with the electronic circuitry part 4. The light-emitting diodes 6 may be used to increase the 35 illumination.

The light-sensitive optical sensor 8 may be a two-dimensional CMOS unit or CCD unit (CCD = Charge Coupled

Device) with a built-in AD converter. Such sensors are commercially available. The sensor 8 may be mounted on a printed circuit board 11.

The power supply to the device is obtained from a battery 12 which is mounted in a separate compartment 13 in the casing.

Fig. 2 is a block schema of the electronic circuitry part 4, which comprises a processor 20 which, via a bus 21, is connected to a read-only memory ROM 22, in which the program of the processor is stored, to a write/read memory RAM 23, which is the work memory of the processor and in which the images from the sensor as well as characters that are interpreted from the recorded images are stored, to a control logic unit 24 and to the sensor 8.

The control logic unit 24 is connected to a number of peripherals, such as a display 25 mounted in the casing, an IR transceiver or short-range radio link 26 for transferring information to/from an external computer, buttons 27 by means of which the user can control the device, and an operation indicating device 28 consisting of a second set of light-emitting diodes which may indicate whether recording occurs or not and other operating conditions. The control logic unit 24 generates control signals to the memories, the sensor and the peripherals. The control logic unit also manages the generation and the prioritization of interrupts to the processor. The buttons 27, the transceiver 26, the display 25 and the light-emitting diodes 6 are controlled by the processor by writing and reading in the records of the control logic unit. The buttons 27 generate interrupts to the processor 20 when activated.

The function of the device will now be described. A sheet of paper 9 is provided with a plurality of lines of printed text 10 as shown in Fig. 3. When a user activates the scanner pen by means of the buttons 27 and passes it across the sheet of paper with the opening 2 directed

towards the sheet of paper, three images 14, 15, 16 are recorded. Each of the images 14, 15, 16 is exposed to OCR processing and the text of the images is converted into sets of characters as illustrated in Fig. 8. Subsequently the sets of characters are assembled or stitched so as to form a complete text. As shown in Fig. 3, the images 14, 15, 16 may be rotated in relation to each other. Thus, a first image 14 is turned or rotated in relation to a second image 15, which in turn is rotated in relation to a third image 16.

In order to optimize the optical character recognition in the recorded images 14, 15, 16 it is advantageous to know the orientation of the lines of text in the image. Therefore, the orientation of the lines of text is detected before the character recognition is carried out.

The detection of the orientation of the lines of text may be carried out using the Hough transformation.

Referring to Figs 4 and 5, the Hough transformation will now be generally described. Fig. 4a shows five points in a plane with the coordinate axes X and Y. Fig 4b shows the Hough transform of the five points in Fig. 4a. A first point 18a has a first Hough transform curve 19a which describes all the straight lines extending through the first point 18a in Fig. 4a as a function of the parameters θ and ρ where θ is the angle of the straight lines through the point and ρ is the distance of the straight lines from origin. The Hough transform curves have a sinusoidal shape. Correspondingly, the second 18b, third 18c, fourth 18d and fifth 18e points have a second 19b, third 19c, fourth 19d and fifth 19e Hough transform curve. The second 19b, third 19c and fourth 19d Hough transform curves in Fig. 4b intersect in a point. This point in Fig. 4b corresponds to a straight line in Fig. 4a extending through both the second point 18b and the third point 18c and the fourth point 18d.

Fig. 9 shows the second recorded image 15 from Fig. 3, which consists of a plurality of pixels in which

lines of text are to be found. For each black pixel in the second recorded image 15, a Hough transform curve is calculated. The Hough transforms are inserted in one and the same diagram.

- 5 Fig. 9 shows a first line 32 and a second line 33. Lines having approximately the same direction as the first line 32 will intersect a larger number of points than lines having approximately the same inclination as the second line 33 since the dark pixels in the recorded
10 image 15 are positioned along lines of text having approximately the same direction as the first line 32.

- Fig. 5 illustrates that the maximum number of intersections can be used to determine the orientation of the lines of text. The circles 73 correspond to points
15 in the Hough transform diagram where several Hough transform curves of points in Fig. 9 intersect, i.e. maximum of intersections. The circles 73 corresponds to the image 15 and are positioned along a straight line 34. From the distance between the circles 73, the distance
20 between the lines of text can be determined. The position of the intersecting line 34 along the θ axis indicates the rotation of the recorded image. The second line 35 in Fig. 5 corresponds to the image 14 and extends through a plurality of maximum indicated by crosses 36 in the
25 diagram. The inclination of the second line 35 indicates that the image has a perspective, i.e. the lines of text have different rotations. Also the slight different distances between the crosses 36 indicate that the image has a perspective with larger distances between the lines
30 at the lower portion of the line 36. The displacement of the second intersecting line 35 in relation to the first line along the θ axis indicates that the lines of text are rotated in the recorded image. By means of this information, the image may be adjusted for perspective
35 and rotated, for example to the horizontal direction, which is the same direction as image 15. As appears, image 15 corresponding to line 34 need no adjustment,

while image 14 corresponding to line 35 needs adjustment of the perspective to make line 36 vertical and with approximately equidistant crosses 36 and adjustment as to the rotational position, to move line 35 to the same
 5 angle θ as image 15, which may correspond to zero angle.

After identification of the lines of text, an identification of the start and end parts of the words in the recorded image is carried out. Fig. 6 indicates how the letter "e" 37 is detected. As shown in Fig. 6, the number
 10 of dark pixels 7 are counted in the vertical direction perpendicular to the line 38, which may be calculated as described above. The number of dark pixels is zero up to the start 39 of the letter "e" and will again be zero at the end 40 of the letter "e". When the number of dark
 15 pixels has been zero for a predetermined period, this is detected as the end of a word.

With reference to Fig. 7, the words are indicated as rectangles, the start 41 of the rectangles indicating the start of a word and the end 42 of the rectangles
 20 indicating the end of a word. Fig. 7a corresponds to a first recorded image 14 and Fig. 7b corresponds to a second recorded image 15. A length of a first word 43 in Fig. 7a has correspondence in a length of a second word 44 in Fig. 7b. Correspondingly, a length of a third
 25 word 45 in Fig. 7a has correspondence in a length of a fourth word 46 in Fig. 7b. By matching the two images, it is possible to find out how the recorded images overlap each other, by only using the graphical information of the length of each word.

30 Thus, by using the length of the words for each line, it is possible to carry out a rough putting-together or stitching or assembling of the two images. The images are roughly assembled so that a sequence of word lengths in the first recorded image corresponds to a
 35 sequence of word lengths in the second recorded image. The word lengths along different lines in the first recorded image should thus correspond to word lengths

along corresponding lines in the second recorded image. In this way, it is possible to determine how the images are displaced relative to each other.

Fig. 3 shows how this may be used to sort out unnecessary images so that optical character recognition need not be carried out as regards all images that are recorded. A first image 47 and a second image 49 completely overlap the area which is covered by a third recorded image 48 which is indicated by dashed lines. By using the method as described in connection with Fig. 7, the third recorded image 48 can be completely omitted, without optical character recognition being carried out. Of course, Fig. 3 is only schematic, since the images often overlap each other to a much larger extent. Indeed, if the scanner pen is held approximately still, all images overlap more or less, and a substantial saving of computing power may be obtained by omitting images with duplicate information. On the other hand, during normal scanning operation, a partial overlap may be used for sorting out errors in the optical character recognition process or the assembling process, in which case overlapping images are not omitted or discarded.

Another method of assembling the images is disclosed in Fig. 8, which shows a first set of characters 50 with a plurality of characters 60 corresponding to the first recorded image 47 in Fig. 3 and a second set of characters 51 with a plurality of characters 61 corresponding to the second recorded image 49 in Fig. 3. The text in the first set of characters and the second set of characters follows the direction of the lines of text 62, which may have been obtained by the Hough transform process described above. The first set of characters 50 and the second set of characters 51 are put together or assembled by comparing characters in the two sets of characters. Firstly, the first character 52 in the first set of characters is compared with each of the characters in the second set of characters 51. The operation

proceeds correspondingly for the second character 63 and the third character 64 in the first set of characters 50. Good correspondence is obtained when the characters in the word "skilled" 53 in the second line of the first set of characters is compared with the word "skilled" 54 in the first line in the second set of characters 51. Since a word can appear in many positions in a text, one starts from the first correspondence found and then compares the rest of the text for this position, a total number of points being obtained which indicates how well the two sets of characters correspond for this position. Subsequently this step is repeated for the next position where correspondence is obtained. Finally, the position is selected in which the total number of points indicates the best correspondence. In Fig. 8, the text is in English but a person skilled in the art understands that the text could just as well be in any other language and that the text in Fig. 8 is only used to illustrate the function of the device. The image may also comprise symbols, such as mathematical expressions, or even line art, to a limited extent.

The two assembling methods may be combined, so that the images are first compared in a rough manner and then on character level. In this way, it will be possible to carry out assembling in two dimensions with limited computing power. If the reading device is first moved to the right like in Fig. 3 and then down and to the left, a larger surface is obtained which is to be assembled in two dimensions. By determining the mutual relationship of the partial images by rough assembling and then on character level, it is relatively easy to obtain both horizontal and vertical assembling. The characteristic that the lines determine the vertical position with great accuracy results in the possibility of alignment.

Each assembling method may alternatively be used separately. If the method using length of words is used separately, the images may be assembled into a composite

image before final conversion of the images to characters by optical character recognition. This method may be used when the images comprises other matter than text, such as small pictures or symbols. In this case, the symbols or
 5 small pictures will be handled as if they were words and be included in a rectangle. The assembling process will work, provided that the pictures or symbols are sufficiently small. However, the OCR process will fail to recognize the rectangle as characters, and then the pixel
 10 representation may be used instead. Other types of boarders may be used than rectangles, such as an area delimited by more than four straight lines or even curved lines.

If the assembling is carried out after the
 15 conversion of each image to character code such as ASCII, small pictures and symbols may be handled separately, at least if they are surrounded by text matter in each image.

As appears from Fig. 7, the images may be processes
 20 by division of the image in boarders, such as rectangles. Each rectangle comprises a complete word or a symbol or a picture surrounded by white areas. Several pictures are compared for finding a succession of rectangles which corresponds to the wanted text. When overlapping
 25 positions have been determined, each rectangle is given a succession number, comprising the line number and the word number on that line. Thus, in Figs. 7a and 7b, the word 41 obtains designation 1:1, the next word 1:2, and the following word 1:3. On the second line, the first
 30 work obtains the designation 2:1, the second word 2:2, the third word 2:3 and the fourth word 2:4. Correspondingly, on the third line, the first word obtains designation 3:1, the second word 3:2, the third word 3:3 and the fourth word 3:4. It is now recognized
 35 that the fourth word on the second row, 2:4 corresponds to the second word on line 2 of Fig. 7b, which means that the first word at the second line of Fig. 7b obtains

designation 2:3, the second word 2:4 (corresponding to the fourth word of line 2 of Fig. 7a), the third word 2:5 and the fourth word 2:6. The same goes for the third line of Fig. 7b, in which the first word obtains designation 3:3, the second word 3:4, the third word 3:5 and the fourth word 3:6. The words are then arranged in a row of words forming a complete line.

It can now be seen that several words are duplicated in the two pictures, namely word 2:4 and word 3:4. There are further words which are duplicated on the other lines. These duplications may be omitted and replaced by a single word. Else the duplications may be kept and used for increasing the OCR interpretation accuracy.

Finally, the words are OCR processed in the right order to obtain the desired text.

If any rectangle is larger in the vertical direction than a single line, it may obtain designation like 2,3:6, if it occupies lines two and three. In this way, larger objects such as pictures or symbols may be handled.

There are a number of cases in which partial words are included in Fig. 7a but included in full in Fig. 7b, such as word 1:3. In this case, the longest version of the word is used for interpretation. If there is a doubt if this is correct, all fragments may be used to recreate the complete word.

In this way, the images are assembled on a word basis starting from the pixel representation and dividing the image inside boarders, such as rectangles which are compared for the best overlapping position. Then, duplicate information is omitted or used for further accuracy and then the words are arranged in the right order and finally converted to ASCII-code.

Pictures or symbols which may not be recognised by the OCR program, may be maintained in pixel format and displayed as such in the final picture. For increased safety, also at least one version of the words may be kept in pixel format in parallel with the OCR-version,

especially if the OCR program indicates a poor quality of processing.

Every new image is compared with previous information in order to find out its orientation therein.

- 5 Thus, each image is processed both in the vertical direction as well as in the horizontal direction, both forwards and backwards. Thus, it is possible to scan in two dimensions by the present invention. This is possible because of the division of the image in a coded
10 representation which is less time consuming to process, either in the form of rectangles or similar or in the form of ASCII code.

- It may be of interest to have some kind of feed-back that the desired information is gathered. This may be
15 accomplished by displaying the assembled information at the screen. However, since the display at a handheld device is rather small, another method would be to display the lines as a succession of pixels at the display, in which one pixel approximately corresponds to
20 a single character. Then, the characters will form words and the layout of words would give a visual indication of the scanned surface. If the processing comprises division into rectangles, these rectangles may be indicated as they are assembled.

- 25 Figs 11a, 11b and 11c show how this may be accomplished. Fig. 11a is a text that is to be scanned. Fig. 11b is the division of this text in rectangles. Finally, Fig. 11c is the representation of the rectangles at a small display, in which rectangles are indicated in
30 black pixels and spaces between the rectangles as gray pixels. From Fig. 11c it can be seen that some information is missing as indicated by white pixels 29. The user then directs his scanner pen towards the area missing until the display indicates that all areas are
35 fully covered by at least one image. Finally, the complete image is converted to ASCII, if that has not been done earlier in the process.

If the assembling is done by using the coded representation in the nature of ASCII code, each decoded character is displayed as a black dot on the display screen, while spaces are displayed as grey dots. Any white dot will indicate that information is missing, as described above.

According to the present invention, it is required that the information at least partially is positioned along identifiable lines. If the device is passed across a photograph or some other surface which is not divided into lines, this can easily be recorded by the processor in the device, and this part of the image may be discarded or stored separately as an picture or photograph. If said surface is completely or at least partially surrounded by lines, it would be possible to handle the situation via the invention, as soon as at least a portion of a line is included in every image.

Fig. 10 is a flow chart of the operation of a computer program according to the invention. The computer program is adapted to be executed in the electronic circuitry part 4 of the device. In a first step 55, digital images are received from the sensor 8. In a second step 56, the digital images are converted into strings of characters using character recognition. In a third step 57, the strings of characters are assembled or put together.

It is not necessary to carry out the rough putting-together of the recorded images as described in connection with Fig. 7, and optical character recognition can be carried out directly as regards the recorded images. Moreover, the orientation of the lines of text need not be identified in the recorded images if an optical character recognition algorithm is used which is able to identify characters also when the lines of text are rotated.

A person skilled in the art realizes that the invention is not limited to the embodiments shown and that

many modifications are feasible within the scope of the invention. The invention is only limited by the appended patent claims.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230